



UNIX Platforms

Computer Hardware

- **CPU:** RISC 90 MHz or higher, Intel® 300 MHz or higher
- **Memory:** 128 MB RAM (256 MB recommended)
- **Hard disk space:** 100 MB permanent disk space plus 100 MB additional temporary space required during installation
- **Network Interface Card:** 10baseT or higher, configured with the latest drivers for your platform

Fax Hardware

- Dialogic® Brooktrout® SR140 fax software, TruFax®, TR1034™ digital or analog fax board with Red Hat® Enterprise 4 and 5 only
- Dialogic® Diva Server™ fax board (Linux only)
- Multitech and Digi Fax modem class 2, 2.0, 2.1

Qualified and recommended platforms

- Sun Solaris SPARC® 9 (32-bit or 64-bit with SPARC v8/32-bit applications support)
- Sun Solaris® Intel 10 (32-bit or 64-bit with x86/32bits applications support)
- IBM Aix 5.1 and 6.1
- HP-UX 11i v1 (B.11.11)
- SCO Open Server™ 5.0.7 and 6.0
- SCO UnixWare® 7.1.3
- Red Hat® Enterprise 3, 4 and 5

Outsourced fax

- Fax on Demand Connector to send faxes through the Esker outsourced fax service
- Uses HTTPS Internet connection, no proxy server

WINDOWS Platforms

Computer Hardware

- **CPU:** Pentium III 450 MHz or higher
- **Memory:** 128 MB RAM (256 MB recommended)
- **Hard disk space:** 120 MB permanent disk space plus 100 MB additional temporary space required during installation
- **Network Interface Card:** 10baseT or higher, configured with the latest drivers for your platform

Fax Hardware

- Dialogic® Brooktrout® SR140 fax software, TruFax®, TR1034™ digital or analog fax board
- Dialogic® Diva Server™ fax board
- Multitech and Digi Fax modem class 2, 2.0, 2.1

Qualified and recommended platforms

- Microsoft® Windows Server™ 2003 R2 SP2 (32-bit version only) or Microsoft® Windows Server™ 2003 SP2 (32-bit Standard Edition, Enterprise Edition, or Datacenter Edition)
- Microsoft® Windows Server™ 2008 SP1 (32-bit and 64-bit Standard Edition, Enterprise Edition, or Datacenter Edition)
- Microsoft® Windows XP SP3 (32-bit version only)
- Microsoft® Windows Vista SP1 (32-bit and 64-bit versions)

Outsourced fax

- Fax on Demand Connector to send faxes through the Esker outsourced fax service
- Uses HTTPS Internet connection, no proxy server

©2009 Esker S.A. All rights reserved. Esker, the Esker logo and VSI-FAX are trademarks or registered trademarks of Esker S.A. in the U.S.A., France, and other countries. All other trademarks are the property of their respective owners.